





NOTE

7

EXCAVATOR

ADDRESS:

DETAILED HYDRANT LOCATION LOCATION MAP ATTACHED

NO PERSON SHALL ENTER THE TRENCH UNLESS ALL PROVISIONS OF OSHA 1926 ARE METI ALL EXPOSED PVC SURFACES SHALL BE PAINTED WITH REFLECTIVE MATERIAL.

REFERENCE THE ATTACHED STANDARD "DRY HYDRANT"

NOTES:

- CHECK WITH LOCAL FIRE DEPARTMENT FOR APPROVED TYPE OF CONNECTION
 USE 20' LENGTH SECTION OF PIPE INTO WATER.
- 16 ft. RECOMMENDED (NFPA 1142)

 GEOTEXTILE MNDOT NONWOVEN CLASS V



<u>ALL—WEATHER ROAD DETAI</u>

UNDERWATER SUPPORT AND ANCHOR

(other type pipe support and anchor may be approved)

COUNTY:

DRY HYDRANT

LANDOWNER:

COUNTY:

DESIDED

MATURAL RESOURCES

CONSERVATION SERVICE

MITTE

MAINTAIN 30 IN. FROST DEPTH (J PIPELINE -(2) - STANDPIPE 4 NOT TO NORMAL WATERLINE ELEV. SCALE (G) (J) M တ္ ₹ 2 ft. MIN. 2 ft. APPROVAL DATE: STANDARD DRAWING NO.: 6 - INTAKE STRAINER 똧 ANTICIPATED LOW WATER LEVEL - ELEV. 1/06 MN-ENG-306C CHECKED

POST PROTECTION -

.#

SUCTION HOSE SUPPORT

-ALL-WEATHER

-()

CENTERLINE PUMP INTAKE

STANDPIPE

DETAIL

(A)

EXISTING GROUND

ROAD (SEE DETAIL) (10)